## EUROPEAN PATENT OFFICE

## **Patent Abstracts of Japan**

**PUBLICATION NUMBER** 

10321666

**PUBLICATION DATE** 

04-12-98

APPLICATION DATE

16-05-97

APPLICATION NUMBER

09143130

APPLICANT: NEC CORP;

INVENTOR: OTAKE KENICHI;

INT.CL.


H01L 21/60 H01L 21/56 H03H 9/25

TITLE

**RESIN SEALING STRUCTURE OF FLIP** 

CHIP MOUNTING TYPE

SEMICONDUCTOR ELEMENT



ABSTRACT :

PROBLEM TO BE SOLVED: To improve yield and increase resistance to vibration and shock, by flip chip mounting a semiconductor element having a dam on a substrate having a dam, forming a hollow structure between the semiconductor element and the facing substrate, and covering the semiconductor element with resin.

SOLUTION: A semiconductor element 2 on which a dam 8 is formed is flip chip mounted on a substrate 1 on which a dam 4 is formed. The semiconductor element side dam 8 is positioned inside the substrate side dam 4. The semiconductor element 2 is covered with resin 7. A gap between the substrate 1 and the semiconductor element 2 is turned into a hollow airtight structure. The semiconductor element 2 is flip chip mounted on the substrate 1, and a chip side pad 6b is bonded to a substrate side pad 6a via a bump 5. When a gap distance between the substrate 1 and the semiconductor element 2 is increased by the warp of the substrate 1 and the semiconductor element 2, resin 7 does not permeate and is prevented from coming into contact with an electrode pattern 3 on the semiconductor element 2 surface.

COPYRIGHT: (C)1998, JPO